

8500

DC BATTERY BACKUP CAPABLE WALL MOUNT GARAGE DOOR OPENER

Wall Mount Design: The simple beauty of an open space.



KEY FEATURES

SPACE-SAVING

Design Maximizes Versatility

LIFTING POWER

Powers 650 lbs. Doors!

SMART

MyQ® MOBILE APP LETS USERS RECEIVE ALERTS AND CONTROL THE OPENER FROM ANYWHERE WHEN PAIRED WITH THE MYQ INTERNET GATEWAY (828LM SOLD SEPARATELY).

QUIET AND RELIABLE

WALL MOUNT DESIGN AND QUIET DC MOTOR ELIMINATE NOISE AND VIBRATIONS THROUGH THE CEILING AND PROVIDES SMOOTH OPERATION.

LIFTING POWER OPERATES DOORS UP TO 650 LBS.

BATTERY BACK-UP CAPABLE TO ENSURE ACCESS EVEN WHEN THE POWERS OUT. (475LM SOLD SEPARATELY).

REMOTE LIGHT DELIVERS 200 WATTS OF LIGHT WITH ADJUSTABLE LIGHT TIME DELAY.

WARRANTY LIFETIME MOTOR, 5-YEAR PARTS.

SECURE

TIMER-TO-CLOSE AUTOMATICALLY CLOSES THE DOOR AFTER A PRESET AMOUNT OF TIME.

SECURITY+ 2.0® SENDS A NEW CODE WITH EVERY REMOTE CONTROL CLICK.

MOTION DETECTOR AUTOMATICALLY TURNS ON THE LIGHT.

THE PROTECTOR SYSTEM® AUTO-REVERSES THE DOOR IF THERE'S AN OBSTRUCTION.

POWER LOCK DEADBOLT ENSURES THE DOOR CANNOT BE FORCED OPEN.

INCLUDED ACCESSORIES:

3-BUTTON REMOTE CONTROL

Operates up to 3 openers or MyQ Light Accessories.



893MAX

MYQ® CONTROL PANEL

Equipped with the Timer-to-Close feature, which automatically closes the garage door after a pre-programmed number of minutes. Motion detector activates the garage door opener lights.



888LM

REMOTE LIGHT

Place anywhere in the garage for additional lighting.



380LM

POWERFUL ADD-ONS:

INTERNET GATEWAY

Connects the opener to the Internet, enabling smartphone control.



828LM

REMOTE LIGHT CONTROL

Enables home lighting control through the garage remote or a smartphone.



825LM

GARAGE DOOR AND GATE MONITOR

Monitors and closes up to 4 garage doors from any room in the house.



829LM

BATTERY BACKUP

Powers up even when power is out so you can get in your garage.



475LM

PRODUCT GUIDE 8500

DC BATTERY BACKUP CAPABLE WALL MOUNT GARAGE DOOR OPENER

LiftMaster®

MASTERFUL ENGINEERING.

MOTOR



- Heavy-Duty 24V DC
- Automatic Thermal Protection
- Permanent Lubrication

POWER



- 120V AC
- 60 Hz Voltage
- 2.7A Current Rating
- UL® Listed
- 6' Power Cord (3-Prong)

MECHANICS



- **Steel Chassis and Plastic Cover**
- **Internal Chain and Sprocket Drive Mechanism** (63:1 Gear Reduction)
- **Auto-Force** Adjustment for Changing Weather and Environmental Conditions
- **Electronic Limits** for Easy Setup

STANDARD SPECS.



16.25"

DIMENSIONS

Max. Door Height: 14 ft.
Headroom Clearance Required: 3 in. from Center of Torsion Bar

DC BATTERY BACKUP CAPABLE WALL MOUNT GARAGE DOOR OPENER



MAX. DOOR WEIGHT
650 lbs.†

8.5"

Per second for door to move upward

SPEED

7.6"

Per second for door to move downward

SECURITY

SECURITY+ 2.0®

RADIO CONTROLS

Operating Range: ~200'

Operating Temperature: -40°F to 150°F

3-Button Remote Control (893MAX)

- Remote Control: 310, 315 and 390 MHz Tri-Band*
- Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- Anti-Burglary Coding

*Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

ENCRYPTED CONTROLS

MyQ® Control Panel® (888LM)

- MyQand Security+ 2.0 Radio
- Timer-to-Close
- Motion Detecting: Hands free opener lights on
- Light Control: Turns opener lights on/off
- Lock Mode: Locks out remote controls
- Program remote controls, keypads and MyQ Accessories

- *Because the radios reside in the control panel, alternate wired control panels should not be used with this operator.

SMART

MyQ® RADIO



- Provides 2-way communication from garage door opener and MyQ accessories*.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.**

*MyQ radio disabled in battery backup mode or when using Alternate Power System (580LM)

**Requires Internet Gateway Accessory Model 828LM

HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER***)

***May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

ELECTRICAL

LIGHTING

REMOTE LIGHT (380LM)



- Remote light control fixture can be located anywhere in garage
- Number of bulbs: 2
- Maximum Wattage: 100 x 2
- Adjustable Time, Solid-State Delay
- (1.5 - 4.5 minutes)

SHIPPING.

SHIPPING WEIGHT (in lbs.)



CARTONS (1)

CARTON 1: 24" x 10" x 12"

- Garage Door Opener Head (8500)
- MyQ Control Panel (888LM)
- 3-Button Remote Control (893MAX)
- The Protector System® Safety Reversing Sensors
- Power Door Lock
- Remote Light (380LM)

SAFETY AND SECURITY.

- The Protector System Safety Reversing Sensors
- Battery Backup Capable compatible model 475LM (optional accessory)
- Alert-2-Close/Unattended Close Operation††
- Motion Detection Feature on Control Panel
- Hands-Free Work Lights On
- Emergency/Quick Release
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 MyQ Devices



Note: to reduce the risk of injury to persons, only use Alert-2-Close/Unattended

††Close Operation features when installed with a sectional door.

© 2017 LiftMaster All Rights Reserved
 300 Windsor Drive, Oak Brook, IL 60523
 LiftMaster.com

Wi-Fi® is a registered trademark of Wi-Fi Alliance
 UL® and the UL logo are trademarks of UL LLC © 2017 All Rights Reserved.
 LMGCA8500 12/17

LiftMaster®