# DC BATTERY BACKUP BELT DRIVE WI-FI® GARAGE DOOR OPENER

Feature rich, offering ultimate garage protection.



### SECURE

AUTOMATIC GARAGE DOOR LOCK CAPABLE: DEADBOLT LOCKS THE GARAGE DOOR. MAKING IT VIRTUALLY IMPENETRABLE (2 MAX., SOLD SEPARATELY).

TIMER-TO-CLOSE CAN BE PROGRAMMED TO CLOSE THE DOOR AFTER A SET AMOUNT OF TIME.

SECURITY+ 2.0® SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY MyQ®.

MOTION DETECTOR LIGHTS THE WAY AUTOMATICALLY.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

### QUIET AND RELIABLE

BELT DRIVE SYSTEM FOR POWERFUL, ULTRA-QUIET PERFORMANCE.

SOFT START/STOP FOR SMOOTH OPERATION.

DC MOTOR IS PURPOSEFULLY DESIGNED FOR QUIET, LONG-LASTING SERVICE.

BATTERY BACKUP ENSURES GARAGE ACCESS EVEN WHEN THE POWER'S OUT.

WARRANTY LIFETIME MOTOR AND BELT, 5-YEAR PARTS, 1-YEAR BATTERY AND ACCESSORIES.

### SMART

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

FREE MYQ MOBILE APP SO USERS KNOW THEIR HOME IS SECURE.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

MONITOR AND CONTROL THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

### **INCLUDED ACCESSORIES:**

#### **SMART CONTROL PANEL®**

LCD display enables simple programming and adjustment of settings.





Operates up to 3 openers or MyQ Light Accessories.



893MAX

#### INTEGRATED BATTERY BACKUP

Powers up the opener when the power's out.



### **POWERFUL ADD-ONS:**

#### **AUTOMATIC GARAGE** DOOR LOCK CAPABLE

Deadbolts the garage door automatically every time it closes.



#### REMOTE LIGHT CONTROL

Plug in any lamp to this device to control it with a smartphone or garage remote.



#### MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access.





#### WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN.



DC BATTERY BACKUP BELT

### MASTERFUL ENGINEERING.

#### MOTOR



-12V DC

-53 RPM

MECHANICS

-Automatic Thermal Protection

-Permanent Lubrication

- Steel Chassis, T-Rail and Trolley

and Environmental Conditions - Electronic Limits for Easy Setup

- Full Reinforced Belt Drive Mechanism

(63:1 Gear Reduction and Adjustable Door Arm) - Auto-Force Adjustment for Changing Weather

- DC Wi-Fi Logic Board with Built-In Surge Suppressor


(for Replacement Logic Boards, Order Part 050DCTWFLK)

#### POWER -



- -120V AC
- -60 Hz Voltage
- -2.7A Current Rating
- -UL Listed
- -6' Power Cord (3-Prong)

#### **DIMENSIONS**



Headroom Clearance Required: 2"



911 Per second for door

> to move upward

**SPEED** 

Per second for door to move downward

Rail Options	7'	8'	10'
Installed Length	125"	140"	164"
Max. Opening	7'6"	8'6"	10'6"

-2 Lock Terminals Allow up to 2 Locks to Be Connected (Sold Separately)

### STANDARD SPECS.

#### SECURITY+ 2.0®

RADIO CONTROLS

■ Operating Range: ~200 

Operating Temperature: -40°F to 150°F

- 3-Button Remote Control (893MAX)
- -Remote Control: 310, 315 and 390 MHz Tri-Band\*
- -Garage Door Opener: Frequency Agile on 310, 315 and 390 MHz
- -Anti-Burglary Coding
- \*Tri-band on Security+ 2.0 coding only. Premium remote control is backwards compatible to all LiftMaster® openers manufactured since January 1993.

#### **ENCRYPTED CONTROLS**

Smart Control Panel® (880LMW)

- -Timer-to-Close
- -Program Remote Controls, Keypads
- and MyQ Accessories
- -Maintenance Alert System
- -Easy Wi-Fi Setup

#### MyQ® RADIO



- Provides 2-way communication from garage door opener and MyQ Accessories.
- Enables monitoring and control of garage door openers and lighting controls via smartphone, tablet or computer.

#### **HOMELINK® COMPATIBLE** (VERSION 4.0 OR HIGHER\*)

\*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

#### LIGHTING





- Max. 2 100-Watt Lightbulbs
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts
- Disabled in Battery Backup Mode

### SHIPPING.

## (in lbs.)











GARAGE (OPTIONAL)

-Garage Door Opener Head (8550W)

-Smart Control Panel (880LMW)

-3-Button Remote Control (893MAX)

-The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Belt T-Rail

CARTON 3: 5.31" x 4.63" x 5.13"

-Battery (485LM)

LMGDENPG8550A 0617

CARTON 4 (OPTIONAL): 8" x 4.5" x 4"


-Automatic Garage Door Lock (841LM)

#### SAFETY AND SECURITY.

- Automatic Garage Door Lock Capable (2 Max.)
- Alert-2-Close/Unattended Close Operation<sup>†</sup>
- Motion Detection Feature on Control Panel
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening

- Down Safety Reverse
- Up Safety Stop
- Safety Beam Obstruction Turns Lights On
- Maintenance Alert System
- Garage Door Opener Capacity of up to 40 Remote Controls, 4 Wireless Keyless Entry Systems and 16 MyQ Devices











CARTON 1: 20" x 12" x 10"









BACKUP

BATTERY AUTOMATIC DOOR LOCK

